

Safety Data Sheet according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

1 Identification

- **Product identifier**
- **Trade name:** 5150 FAST DRY PRIMER GREY
- **Article number:** 5150
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

UCP PAINT INC.
19500 Rte Transcanadienne
Baie D'Urfe, H9X 3S4, Quebec, Canada
(514) 457-1512

- **Information department:** Product safety department
- **Emergency telephone number:** Chemtrec: 24 Hours 1-800-424-9300

2 Hazard identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids - Category 2

H225

Highly flammable liquid and vapour.



GHS08 Health hazard

Reproductive Toxicity - Category 2

H361

Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure - Category 1

H372-H373

Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.

Aspiration Hazard - Category 1

H304

May be fatal if swallowed and enters airways.



GHS07

Skin Sensitizer - Category 1

H317

May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 1)

· **Hazard pictograms**· **Signal word** *Danger*· **Hazard-determining components of labeling:***Solvent naphtha (petroleum), light aliph.**toluene**Stoddard solvent**A mixture of: butan-2-one oxime and syn-O,O'-di(butan-2-one oxime)-diethoxysilane*· **Hazard statements***Highly flammable liquid and vapour.**May cause an allergic skin reaction.**Suspected of damaging fertility or the unborn child.**Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.*· **Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**Use explosion-proof [electrical/ventilating/lighting] equipment.**Do not breathe dust/fume/gas/mist/vapours/spray.**Wear protective gloves/protective clothing/eye protection/face protection.**Ground and bond container and receiving equipment.**Keep container tightly closed.**Use non-sparking tools.**Take actions to prevent static discharges.**Wash thoroughly after handling.**Do not eat, drink or smoke when using this product.**Contaminated work clothing should not be allowed out of the workplace.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**IF SWALLOWED: Immediately call a POISON CENTER/ doctor.**IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].**Specific treatment (see on this label).**IF exposed or concerned: Get medical advice/attention.**If skin irritation or rash occurs: Get medical advice/attention.**Get medical advice/attention if you feel unwell.**Do NOT induce vomiting.**In case of fire: Use for extinction: CO₂, powder or water spray.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Store in a well-ventilated place. Keep cool.**Dispose of contents/container in accordance with local/regional/national/international regulations.*· **Hazard description:**· **WHMIS-symbols:***B2 - Flammable liquid*

(Contd. on page 3)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 2)

D2B - Toxic material causing other toxic effects



- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *1
Fire = 3
Reactivity = 0

3 Composition/Information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

64742-89-8	Solvent naphtha (petroleum), light aliph.	10-30% w/w
64742-49-0	Naphtha (petroleum), hydrotreated light	5-<10% w/w
142-82-5	heptane	1-5% w/w
8052-41-3	Stoddard solvent	1-5% w/w
64742-47-8	Distillates (petroleum), hydrotreated light	0,5-1,5% w/w
108-88-3	toluene	0,5-1,5% w/w
96-29-7	A mixture of: butan-2-one oxime and syn-O,O'-di(butan-2-one oxime)-diethoxysilane	0,1-<1% w/w

4 First aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

CA

(Contd. on page 5)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 4)

8 Exposure controls/ Personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

142-82-5 heptane

EL	Short-term value: 500 ppm Long-term value: 400 ppm
EV	Short-term value: 2,045 mg/m ³ , 500 ppm Long-term value: 1,635 mg/m ³ , 400 ppm

8052-41-3 Stoddard solvent

EL	Short-term value: 580 mg/m ³ Long-term value: 290 mg/m ³
----	---

64742-47-8 Distillates (petroleum), hydrotreated light

EL	Long-term value: 200 mg/m ³ Skin
----	--

108-88-3 toluene

EL	Long-term value: 20 ppm R
EV	Long-term value: 20 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Grey
Odor:	Aromatic
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>94 °C

· Flash point: 4 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapor pressure: Not determined.

Density at 20 °C:	1,32 g/cm ³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Organic solvents: 31,2 %

Solids content: 50,7 %

(Contd. on page 7)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 6)

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:**

7779-90-0 trizinc bis(orthophosphate)

Oral LD50 >5000 mg/kg (rat)

· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** Irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
108-88-3	toluene	3
1330-20-7	xylene	3
14808-60-7	Quartz (SiO ₂)	1
100-41-4	ethylbenzene	2B
1333-86-4	Carbon black	2B
136-52-7	cobalt bis(2-ethylhexanoate)	2B
7631-86-9	silicon dioxide, chemically prepared	3

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

12 Ecological information

· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, TDG, IMDG, IATA | UN1263 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · TDG · IMDG · IATA | Paint
1263 Paint, ENVIRONMENTALLY HAZARDOUS
PAINT (HEPTANES, trizinc bis(orthophosphate)), MARINE
POLLUTANT
PAINT |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | |
|  | |
| <ul style="list-style-type: none"> · Class · Label · TDG, IMDG | 3 Flammable liquids
3 |
|   | |
| <ul style="list-style-type: none"> · Class | 3 Flammable liquids |

(Contd. on page 9)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 8)

· **Label** 3· **IATA**

· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**
 · **DOT, TDG, IMDG, IATA** II

· **Environmental hazards:** Product contains environmentally hazardous substances: heptane, trizinc bis(orthophosphate)

· **Marine pollutant:** Yes
 Symbol (fish and tree)

· **Special marking (TDG):** Symbol (fish and tree)

· **Special precautions for user** Warning: Flammable liquids
 · **Danger code (Kemler):** 33
 · **EMS Number:** F-E, S-E
 · **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**
 · **Quantity limitations** On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

· **TDG**
 · **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **IMDG**
 · **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 · **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

7779-90-0 trizinc bis(orthophosphate)

108-88-3 toluene

(Contd. on page 10)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 9)

1330-20-7	xylene
67-56-1	methanol
100-41-4	ethylbenzene
136-52-7	cobalt bis(2-ethylhexanoate)
111-77-3	2-(2-methoxyethoxy)ethanol

· TSCA (Toxic Substances Control Act):

1317-65-3	Calcium Carbonate
142-82-5	heptane
7779-90-0	trizinc bis(orthophosphate)
13463-67-7	titanium dioxide
64742-47-8	Distillates (petroleum), hydrotreated light
108-88-3	toluene
1330-20-7	xylene
67-56-1	methanol
8030-76-0	LECITHIN Lecithins,soya
14808-60-7	Quartz (SiO ₂)
100-41-4	ethylbenzene
1333-86-4	Carbon black
136-52-7	cobalt bis(2-ethylhexanoate)
64742-88-7	Solvent naphtha (petroleum), medium aliph.
21645-51-2	aluminium hydroxide
111-77-3	2-(2-methoxyethoxy)ethanol
107-98-2	1-methoxy-2-propanol
7631-86-9	silicon dioxide, chemically prepared
149-57-5	2-ethylhexanoic acid
79-09-4	propionic acid
7732-18-5	water, distilled, conductivity or of similar purity

· Canadian substance listings:**· Canadian Domestic Substances List (DSL)**

37244-96-5	Nepheline syenite
64742-89-8	Solvent naphtha (petroleum), light aliph.
64742-49-0	Naphtha (petroleum), hydrotreated light
142-82-5	heptane
7779-90-0	trizinc bis(orthophosphate)
8052-41-3	Stoddard solvent
13463-67-7	titanium dioxide
64742-47-8	Distillates (petroleum), hydrotreated light
108-88-3	toluene
1330-20-7	xylene
67-56-1	methanol
8030-76-0	LECITHIN Lecithins,soya

(Contd. on page 11)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 10)

14808-60-7	Quartz (SiO ₂)
100-41-4	ethylbenzene
1333-86-4	Carbon black
136-52-7	cobalt bis(2-ethylhexanoate)
64742-88-7	Solvent naphtha (petroleum), medium aliph.
21645-51-2	aluminium hydroxide
107-98-2	1-methoxy-2-propanol
64742-48-9	Naphtha (petroleum), hydrotreated heavy
7631-86-9	silicon dioxide, chemically prepared
149-57-5	2-ethylhexanoic acid
79-09-4	propionic acid
7732-18-5	water, distilled, conductivity or of similar purity

· **Canadian Ingredient Disclosure list (limit 0.1%)**

100-41-4	ethylbenzene
----------	--------------

· **Canadian Ingredient Disclosure list (limit 1%)**

142-82-5	heptane
8052-41-3	Stoddard solvent
108-88-3	toluene

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light aliph.
toluene

Stoddard solvent

A mixture of: butan-2-one oxime and syn-O,O'-di(butan-2-one oxime)-diethoxysilane

· **Hazard statements**

Highly flammable liquid and vapour.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

Ground and bond container and receiving equipment.

Keep container tightly closed.

(Contd. on page 12)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/12/2017

Reviewed on 07/12/2017

Trade name: 5150 FAST DRY PRIMER GREY

(Contd. of page 11)

Use non-sparking tools.
 Take actions to prevent static discharges.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Contaminated work clothing should not be allowed out of the workplace.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 Specific treatment (see on this label).
 IF exposed or concerned: Get medical advice/attention.
 If skin irritation or rash occurs: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.
 Do NOT induce vomiting.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.
 • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** UCP PAINT
- **Date of preparation / last revision** 07/12/2017 / -
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - WHMIS: Workplace Hazardous Materials Information System (Canada)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative

CA